

DATE:

PROJECT:

COMMENTS:

FEATURES

- Suitable for NEMA 4X applications
- Super-bright, long-life LEDs
- Quick-connect components
- Snap-on canopy for easy installation
- Nickel cadmium battery provides a minimum of 90 minute minimum operation
- Sealed External Momentary test switch and dual diagnostic LED indicator displays AC presence and Hi-Charge status
- Self-Test / Self-Diagnostic monitoring available
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power
- 120/277 VAC field-selectable inputs (with the exception of the C1/C2 (dual circuit) option which requires voltage specification upon ordering)



ORDERING INFORMATION *RWL-AC-G-1-BK-MTEBP*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. FRAME COLOR
RWL	- -	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double	BK Black GY Gray WH White
6. MOUNTING	7. OPTIONS			
MTEBP	-			
MTEBP Universal Mount	BLANK = NO OPTION C1 Dual Circuit - 120 VAC (AC Only) C2 Dual Circuit - 277 VAC (AC Only)	SD Self-Diagnostics (EM Only) HX Internal Heater (120/277 VAC) (EM Only) TP Tamperproof Screws		

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

CONSTRUCTION

- UV Stabilized Polycarbonate housing
- Stainless steel captive screws secure lens cover to housing

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-Type, field selectable chevrons

TEMPERATURE RATING

- From -4°F to 122°F

APPROVALS

- UL 924 Listed for Wet Location
- NFPA Life Safety Code 101
- NFPA 70- NEC
- OSHA

WARRANTY

- Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

DIMENSIONS
