



# SLX-60

ABS Plastic Frame Self Luminous Exit Sign

DATE: [ ]	COMMENTS: [ ]
PROJECT [ ]	[ ]

## FEATURES

- Requires no electricity or external light source
- Maintenance free – no lamps or batteries to replace
- Tamper-proof design
- Easy to install – no wiring required
- Ideal for damp, wet, explosion proof, and extreme temperature applications
- Special wording and pictographs available
- Service life – 10 or 20 year options available



## ORDERING INFORMATION *SLX-60-10-1-BK-BA-MTEBP*

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR
SLX-60	-	-	-	-
	10 10 Years 20 20 Years	1 Single 2 Double	BK Black G Green R Red	BK Black GY Gray WH White
6. MOUNTING	7. OPTIONS			
MTEBP Universal Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount	BLANK = NO OPTION CW Custom Wording VR 1/8" Vandal Resistant Lens (Includes Tamperproof Screws)			

## ACCESSORIES; ORDER SEPARATELY

- WG 5 = Wireguard 15.75" x 14.75" x 6.75"

**CONSTRUCTION**

- Flame retardant, UV stabilized, injection molded ABS frame

**LETTERS**

- 6.0" high; 0.75" stroke

**ARROWS**

- Universal chevrons

**VIEWING DISTANCE**

- 100 ft visibility rating

**TECHNOLOGY**

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas—a natural hydrogen isotope

**WEIGHT**

- Single Face: 2.5 lbs
- Double Face: 5 lbs

**TEMPERATURE RATING**

- From -67°F to 176°F

**APPROVALS**

- UL Listed to standard UL924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class 1, 11, and 111 conditions

**WARRANTY**

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

**DIMENSIONS**
