

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Thin architectural profile
- Illuminates 7 times brighter than UL 924 requirement with super-bright, long-life LEDs and a 25+ year life expectancy
- Battery back-up models without remote heads have a standard 4 hour runtime
- UL listed for damp location
- Optional polycarbonate security cover
- Battery diagnostic system standard — battery status: detects cell failure and issues alert of reduced capacity and the need to replace battery
- Self-Test/Self-Diagnostic monitoring available
- Line latch prevents unnecessary discharge of battery during installation — loads will not illuminate until after application of utility power
- Brownout detection ensures emergency operation during periods of low line voltage
- Sealed, external, momentary test switch and dual diagnostic LED indicator display AC presence and Hi-Charge status
- Zero current, low-voltage disconnect
- Unique, electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life
- Specialty finish available
- 120/277 VAC field-selectable inputs



ORDERING INFORMATION *TLCG2-AC-G-BL-1-BK-BA-MB*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. BACKGROUND COLOR	5. FACE COUNT	6. FRAME COLOR
TLCG2	-	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red W White BL Blue	BL Blue Background CC Custom Color G Green Background R Red Background WH White Background	1 Single 2 Double	BA Brushed Aluminum BK Black CC Custom Color WH White

7. MOUNTING

MB	Back Mount
MPA	12" Pendant Mount
MPB	24" Pendant Mount
MPC	36" Pendant Mount
MPD	48" Pendant Mount
MPE	60" Pendant Mount
MPF	72" Pendant Mount
MTEB	Top/End/Back Mount

8. OPTIONS

BLANK = NO OPTION	
CX	Dual Circuit (120/277 VAC) (AC Only)
SD	Self-Diagnostics (EM Only)
SR	Self-Diagnostics + IR Remote Testing Receiver (EM Only)
EB	Remote Capacity (EM Only)
CW	Custom Wording
CW01	X-Ray In Use
CW02	In Use
CW03	Area of Refuge
CW04	Laser in Use
CW06	Beam On
CW26	Area of Rescue Assistance
FL	Flasher
FA	Fire Alarm Interface
VR	1/8" Vandal Resistant Lens (Includes TP)

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"
- TLRT = Infrared Remote Control

CONSTRUCTION

- Injection molded, internal cavity reflector provides ease of installation and maintenance, together with perfectly even legend illumination
- Heavy duty, two piece walls constructed from die cast aluminum alloy
- Removable front stencil face with overlapping light seal

WEIGHT

- AC: 8 lbs.
- EM: 8 lbs.

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- UL 924
- UL 924 Damp Location
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

Single or Double face sign

