

## TLREM2

Aluminum Thin Line Die-Cast Remote LED Exit Sign

DATE:

PROJECT:

COMMENTS:



### FEATURES

- Remote exit sign is designed to be powered by a master exit sign like the TLRM2, LPDCMR, or ELTMR2.
- Thin architectural profile constructed with die-cast aluminum with specialty finishes available.
- Illuminates 7 times brighter than UL 924 requirement with super-bright, long-life LEDs that have a 25+ year life expectancy.
- UL listed for damp locations.
- Optional polycarbonate security cover is available (see accessories).
- Available with low profile universal mount, back mount, or pendant mount.
- All mountings use standard 4S junction box (not included).
- Unique, electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life.

CEC Title 20



### ORDERING INFORMATION *TLREM2-G-1-BA-MB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FRAME COLOR	5. MOUNTING
<b>TLREM2</b>	-	-	-	-
	<b>G</b> Green <b>R</b> Red	<b>1</b> Single <b>2</b> Double <b>U</b> Universal	<b>BA</b> Brushed Aluminum <b>BK</b> Black <b>CC</b> Custom Color <b>WH</b> White	<b>MB</b> Back Mount <b>MPA</b> 12" Pendant Mount <b>MPB</b> 24" Pendant Mount <b>MPC</b> 36" Pendant Mount <b>MPD</b> 48" Pendant Mount <b>MPE</b> 60" Pendant Mount <b>MPF</b> 72" Pendant Mount <b>MTEB</b> Top/End/Back Mount

### 6. OPTIONS

**BLANK = NO OPTION**

**VR** 1/8" Vandal Resistant Lens (Includes TP)

### ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

NOTE: Wireguards only available with Back Mount.



## SPECIFICATIONS

### CONSTRUCTION

- Injection molded, internal cavity reflector provides easy installation and maintenance together with perfectly even legend illumination.
- Heavy-duty, two piece walls are constructed from die-cast aluminum alloy.
- Removable front stencil face includes overlapping light seal.

### LETTERS

- 6.0" high; 0.75" stroke

### ARROWS

- NFPA type, universal field-selectable chevrons.

### TEMPERATURE RATING

- From 50°F to 104°F

### APPROVALS

- UL 924
- CEC Title 20 Compliant
- UL 924 Damp Location
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

### WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

## DIMENSIONS

