



TLREM2

Aluminum Thinline Die-Cast Remote LED Exit Sign

DATE:

PROJECT:

COMMENTS:



FEATURES

- Thin architectural profile
- Illuminates 7 times brighter than UL 924 requirement with super-bright, long-life LEDs that have a 25+ year life expectancy
- UL listed for damp location
- Optional polycarbonate security cover
- Available with low profile universal canopy, wall mount, or pendant mount
- All mountings use standard 4S junction box (not included)
- Unique, electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life
- Specialty finishes available

CEC Title 20



ORDERING INFORMATION *TLREM2-G-1-BA-MB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FRAME COLOR	5. MOUNTING
TLREM2	-	-	-	-
	G Green R Red	1 Single 2 Double U Universal	BA Brushed Aluminum BK Black CC Custom Color WH White	MB Back Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount MPE 60" Pendant Mount MPF 72" Pendant Mount MTEB Top/End/Back Mount

6. OPTIONS

BLANK = NO OPTION

VR 1/8" Vandal Resistant Lens (Includes TP)

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

CONSTRUCTION

- Injection molded, internal cavity reflector provides easy installation and maintenance, together with perfectly even legend illumination
- Heavy-duty, two piece walls constructed from die-cast aluminum alloy
- Removable front stencil face with overlapping light seal

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA type, universal field-selectable chevrons

WEIGHT

- AC: 8 lbs.
- EM: 8 lbs.

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- UL 924
- CEC Title 20 Compliant
- UL 924 Damp Location
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

