

DATE:

COMMENTS:

PROJECT

FEATURES

- Super-bright, long-life LEDs
- Suitable for damp locations
- Unique pivoting housing suitable for Ceiling, Wall, or End Mount applications
- Recessed backbox kit with adjustable bar hangers included for optional recessed T-Bar or Joist mounting
- Everything you need in the package no matter the mounting configuration
- Includes single face clear lens and double face mirrored lens for versatility
- Additional single face mirrored panel optional
- 120/277 VAC field-selectable inputs
- 4.8V long life Nickel Cadmium, maintenance free battery provides 90 minute runtime
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Zero current low-voltage disconnect
- Energy consumption of less than 2 Watts of nominal power
- Brownout detection ensures emergency operation during periods of low line voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing



ORDERING INFORMATION *UEL-AC-G-1C2M-MTEBR*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. MOUNTING
UEL	-	-	1C2M	MTEBR
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1C2M Single Face, Clear Background and Double Face Mirrored Background	MTEBR Universal Mount

ACCESSORIES; ORDER SEPARATELY

- EUNR1M = Conversion Panel, Single Face, Red Letters, Mirror Background
- EUNG1M = Conversion Panel, Single Face, Green Letters, Mirror Background
- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 6 = Wire guard 20.0" X 17.0" X 12.0"



CONSTRUCTION

- Attractive, low profile satin extruded aluminum
- Gray injection molded end caps and canopy
- Formed sheet steel recessed backbox

INPUT POWER

- AC models: Red <2 watts; Green <3 watts
- EM models: Red <2.5 watts; Green 3 watts

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal field installable, self-adhesive chevrons

WEIGHT

- 3.2 lb

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- UL924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NEC
- OSHA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

DIMENSIONS

