



UEL

Universal Recessed Edge-Lit LED Exit Sign

DATE:

PROJECT

COMMENTS:

FEATURES

- Super-bright LEDs with long life expectancy.
- Suitable for damp locations.
- Unique pivoting housing suitable for ceiling, back, or end mount applications.
- Recessed backbox kit with adjustable bar hangers included for optional recessed T-Bar or joist mounting.
- Includes single face clear lens and double face mirrored lens for versatility.
- Additional single face mirrored panel is optional (see accessories).
- 4.8V long life nickel cadmium, maintenance free battery provides 90 minute runtime.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Zero current low-voltage disconnect used to prevent battery from being overly discharged.
- Energy consumption of less than 2 Watts of nominal power.
- Brownout detection ensures emergency operation during periods of low line voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 120/277 VAC with field selectable inputs.

CEC Title 20



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS

Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION UEL-AC-G-1C2M-MTEBR

UEL-AC-G-1C2M-MTEBR	UEL Universal Recessed Edge-Lit LED Exit Sign, AC Only, Green Letter, Single Face/Clear Background & Double Mirrored Background, Universal Mount
UEL-AC-R-1C2M-MTEBR	UEL Universal Recessed Edge-Lit LED Exit Sign, AC Only, Red Letter, Single Face/Clear Background & Double Mirrored Background, Universal Mount
UEL-EM-G-1C2M-MTEBR	UEL Universal Recessed Edge-Lit LED Exit Sign, Ni-Cad Battery Backup, Green Letter, Single Face/Clear Background & Double Mirrored Background, Universal Mount
UEL-EM-R-1C2M-MTEBR	UEL Universal Recessed Edge-Lit LED Exit Sign, Ni-Cad Battery Backup, Red Letter, Single Face/Clear Background & Double Mirrored Background, Universal Mount

ACCESSORIES; ORDER SEPARATELY

- **EUNR1M** = Conversion Panel, Single Face, Red Letters, Mirror Background
- **EUNG1M** = Conversion Panel, Single Face, Green Letters, Mirror Background
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Attractive, low profile satin extruded aluminum
- Gray injection molded end caps and canopy
- Formed sheet steel recessed backbox

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal field installable, self-adhesive chevrons

INPUT POWER

- AC models: Red <2 watts; Green <3 watts
- EM models: Red <2.5 watts; Green 3 watts

WEIGHT

- 3.2 lbs

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- UL 924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NEC
- OSHA

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General. Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

