

DATE: \_\_\_\_\_  
PROJECT: \_\_\_\_\_

COMMENTS: \_\_\_\_\_



## FEATURES

- 4.0' fixture uses four high-efficiency LED boards
- Available in 3500K, 4000K, or 5000K
- High performance driver operates 100V-277V, 50-60HZ
- Standard surface mount configuration
- Standard 0-10V dimming
- Unit provides 1264 lumens when in battery backup mode



## CONSTRUCTION

- Corrosion, flame and vandal resistant housing
- Integrated stainless steel mounting brackets
- Flat, steel reflector system finished in durable white powder coat
- UV stabilized, polycarbonate diffuser eliminates glare

## APPROVALS

- IP66
- IP65
- NEMA 4X
- UL924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

## WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

## DIMENSIONS



## ORDERING INFORMATION *VTFLED-AC-MT-1L50*

| 1. SERIES | 2. OPERATION                           | 3. MOUNTING   | 4. OUTPUT  | 5. OPTIONS                                 |
|-----------|--|---|--|--|
| VTFLED    | -                                      | -   | -  | -  |
|           | AC AC Only<br>EM Ni-Cad Battery Backup | MT Top Mount<br>MCH 48" Chain Mount<br>MAC50 50" Adjustable Aviation Cable<br>MAC72 72" Adjustable Aviation Cable<br>MAC100 100" Adjustable Aviation Cable<br>MAC150 150" Adjustable Aviation Cable | 1L50(3500K) 50W LED 3500K<br>1L50(4000K) 50W LED 4000K<br>1L50(5000K) 50W LED 5000K<br>1L70(3500K) 70W LED 3500K<br>1L70(4000K) 70W LED 4000K<br>1L70(5000K) 70W LED 5000K | BLANK = NO OPTION<br>TP Tamperproof Screws |

## LAMP OUTPUT

| LAMP TYPE                 | LUMEN OUTPUT | CRI | L70 (HOURS) |
|---------------------------|--------------|-----|-------------|
| 1L50(3500K) 50W LED 3500K | 6138         | >80 | 60,000+     |
| 1L50(4000K) 50W LED 4000K | 6318         | >80 | 60,000+     |
| 1L50(5000K) 50W LED 5000K | 6498         | >80 | 60,000+     |
| 1L70(3500K) 70W LED 3500K | 8593         | >80 | 60,000+     |
| 1L70(4000K) 70W LED 4000K | 8845         | >80 | 60,000+     |
| 1L70(5000K) 70W LED 5000K | 9098         | >80 | 60,000+     |