



## WRH

PAR36 Weather Proof Remote Head

DATE:

PROJECT

COMMENTS:

### FEATURES

- NEMA 4X rating
- Ideal for outdoor and wet locations
- Unique, flex arm design allows for up and down and side to side movement
- Rotary locking collar securely locks lens and reflector assembly into place
- Innovative design allows for quick and easy relamping
- Swivel lock secures adjustable head in place
- Designed to fit most standard junction boxes
- Surface mount on wall or ceiling



### ORDERING INFORMATION WRH-GY-1-L65

1. SERIES	2. HOUSING COLOR	3. HEAD COUNT	4. LAMP SOURCE	5. OPTIONS
WRH	GY GY Gray	1 One Lamp 2 Two Lamps	See Lamp Chart for Part # Example: LED 6V 5W = "L65"	BLANK = NO OPTION TP Tamper-proof Screws

#### ACCESSORIES; ORDER SEPARATELY

- WG 4 = Wireguard 6.0" X 8.0" X 6.0"

### SPECIFICATIONS

#### CONSTRUCTION

- Durable polycarbonate
- Resilient gasketing enables unit to withstand exposure to moisture and corrosive elements

#### APPROVALS

- NEMA 4X
- IP66
- Sanitation Listed
- UL924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

#### WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

### LAMP CHARTS

B - BI-PIN HALOGEN			
	6V	12V	24V
8W	B68	B128	
10W	B610		B2410
12W	B612	B1212	B2412
20W	B620	B1220	B2420
35W		B1235	
50W			B2450
55W		B1255	

M - MR16			
	6V	12V	24V
6W	M66		
10W	M610		
12W		M1212	M2412
20W		M1220	M2420
35W		M1235	M2435
50W		M1250	M2450

L - LED			
	6V	12V	24V
2W		L122	
5W	L65	L125	L245
7W	L67	L127	