



RLP

Damp Location Thermoplastic Pipe Exit & Emergency Combo

DATE:

COMMENTS:

PROJECT

FEATURES

- Damp location listed
- Exceptionally low energy consumption LED light source with 10+ year life expectancy
- Universal canopy included for end, wall, or ceiling mounting
- Remote capability allows for 2W of remote head capacity
- Compatible with Isolite MVH and MVI remote heads
- Available with full self-diagnostic option
- Dual rate charger recharges battery in 24 hours
- Line latch prevents unnecessary discharge of battery during installation
- Integral AC present indicator and push-to-test switch
- Reliable solid state transfer relay
- Two nickel cadmium batteries provide 90 minute emergency run-time
- Electronic control circuit and isolation transformer provide current control and circuit protection, ensuring optimum LED efficiency and life
- 120/277 VAC field-selectable inputs



ORDERING INFORMATION *RLP-G-U-BK-MTEB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	4. FRAME COLOR	5. MOUNTING	6. OPTIONS
RLP	-	U	-	MTEB	-
	G Green R Red	U Universal	BK Black WH White	MTEB Top/End/Back/Mount	BLANK = NO OPTION SD Self-Diagnostics

ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wireguard 14.0" X 10.0" X 4.5"
- WG 3 = Wireguard 14.5" X 6.0" X 10.5"
- WG 10 = Wireguard 13.5" X 12.0" X 16.5"



CONSTRUCTION

- Snap together, Quick fit installation
- Injection Molded, 5VA flame retardant, high impact thermoplastic housing in White or Black finish

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA-Type, field selectable chevrons

TEMPERATURE RATING

- From 32°F to 104°F

APPROVALS

- UL 924
- UL Listed for Damp Location
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS

